

STRONG • EASY • SECURE



An innovation in main runners

Armstrong introduces Peakform, an advanced design of main runner for suspended ceilings.

The new bulb shape and taller profile is designed to create a stronger, stable main runner, making installation both faster and easier.




TRULOK PRELUDE 24 TL


24mm Exposed Suspension System (nominal)

Physical Data


- **Material**
Double-web galvanised steel
- **Surface Finish**
Baked polyester paint
- **Product Family**
Exposed tee system
- **Main Runner/Cross Tee Interface**
TL butt cut ends
- **End Detail**
Main Runner : bulb-to-bulb connection, staked-on **Superlock** clip, single stitching
TL Cross Tee : integral hook, single stitching
- **Fire Rating**
Armstrong have an extensive range of grid and tile products which can provide fire and/or structural protection. Please contact Internal Technical Sales Group for the relevant grid and tile combination.

Accessories


BPA 10230 A* Bottom part of nonius hanger




BPA AWDN 20 A* Bent tee bar hanger for threaded rod



BPA 829 B* Suspension hanger for tee bar



BPA 7898 A* Direct ceiling load clip


Load CapacityMaximum Load = 14kg/m²
(for span (L) deflection limit = L/360)

Test data provided by Stangers Materials Science Laboratories, UK

For other span (L) deflection limits, please multiply the allowable load by the factor indicated:

Span (L) deflection limit	L/300	L/360	L/400	L/500
Multiplier	1.2	1	0.9	0.72

1 BP 31 40 32A 2 BP 11 30 32C 3 BP 11 20 32C

Accessories (continued)


BPA 819 B Locking hold down clip



BPA 7912 40mm soft fibre panel clip




BPA 7902 18/25mm soft fibre panel clip




BPA 820 B Retaining clip for 15mm tiles (Tegular/MicroLook)



BPA 828 B Retaining clip for 15mm Board panels



BPAC 1430 A* Variable placement Hook End Detail



BPA 7878 A* Exterior hold down clip

All measurements in millimetres

* Suitable for Peakform main runners

Please contact Internal Technical Sales Group for further details.

United Kingdom
Armstrong World Industries Ltd.
Building Products Division
Armstrong House
38 Market Square
Uxbridge
Middlesex UB8 1NG
Freefone : 0800 37 18 49
Fax : +44 (0)1895 274 287
www.armstrong-ceilings.co.uk
e-mail: sales-support@armstrong.com

Republic of Ireland
Armstrong World Industries Ltd.
Sales Office
5 The Village Centre
Lucan
Co Dublin
Freefone : 1800 409 002

Africa, Middle East, Turkey Division
Armstrong World Industries Ltd.
Armstrong House
38 Market Square
Uxbridge UB8 1NG
United Kingdom
Tel: +44 (0) 1895 251122
Fax: +44 (0) 1895 272928
<http://ceilings-eu.armstrong.com>

Israel: www.armstrong.co.il
South Africa: www.armstrong-ceilings.za
Turkey: www.armstrong.com.tr
e-mail: sales-support@armstrong.com

All product specifications are subject to modifications without prior notice

PG 2203.1

Armstrong


TRULOK PRELUDE 24 TL

24mm Exposed Suspension System (nominal)


Key Attributes

- **Peakform** patented universal main runner profile for installation either with Prelude TL hook-end cross tees or with Prelude XL stab-end cross tees
- The **Peakform** bulb design increases strength and stability for improved performance
- **Superlock** main runner clip engineered for a strong, secure connection and fast accurate alignment confirmed with an audible click
- Easy to cut thanks to the **Peakform** bulb
- Rotary stitched for additional torsional strength and extra stability during installation
- Slots at 100 mm centres for more flexibility (3600 mm long main runner)
- Prelude TL cross tees with integrally formed hook-on end detail and butt cut joints
- Easy to remove and relocate
- Armstrong Global White

Peakform Main Runner 24 with Superlock Clip




Item Nr.	Dimensions		Content /Carton		Weight/Carton	Carton/Pallet
	length (mm)	height (mm)	pcs	lm	kg	
BP 31 40 32 A*	3600	43	20	72,00	21,00	30
BP 31 43 33 A	3375	43	20	67,50	21,00	30




BP 31 40 32 A*	50	100	33 x 100	100	50
BP 31 43 33 A	337,5	675	2 x 675	675	337,5

Cross Tee Prelude 24 TL Hook System




BP 11 30 32 C *	1200	35	60	72,00	19,50	72
BP 11 30 31 C	1200	35	60	72,00	15,65	72
BP 11 34 33 C	1800	35	60	108,00	36,65	20
BP 11 36 33 C	1500	35	60	90,00	30,70	20
BP 11 33 33 C	1350	35	60	81,00	24,65	72
BP 11 32 33 C	1000	35	60	60,00	22,55	72



BP 11 30 32 C *	300	2 x 300	300
BP 11 30 31 C	300	2 x 300	300
BP 11 34 33 C	300	4 x 300	300
BP 11 36 33 C	300	3 x 300	300
BP 11 33 33 C	337,5	2 x 337,5	337,5
BP 11 32 33 C	250	2 x 250	250

BP 11 20 32 C *	600	35	60	36,00	9,70	144
BP 11 20 31 C	600	35	60	36,00	7,80	144
BP 11 24 33 C	300	35	120	36,00	11,20	144
BP 11 23 33 C	675	35	60	40,50	13,05	144
BP 11 22 33 C	500	35	60	30,00	9,80	144



All measurements in millimetres

*Colours available : Opal (OL), Carrara (CA), Platinum (PN), Black (BK), Red (RD), Blue (BE), Green (GN), Ivory (IY), Aluminium (AL), Brass (BS), Chrome (CE), Brown (BN), White RAL 9010 (WR).

Cross tee alignment is achieved by locating the tees to the right-hand side of the adjoining section.



An innovation in main runners

STRONG

PeakForm™ - strong but light

The new high performance main runner has been engineered to provide a stable, stronger, easier to use product, together with a hot-dipped galvanised steel coating for extra protection.

EASY

PeakForm™ makes it easy

Successful installation is dependant on being able to keep main runners straight and level, this is where Peakform comes into its own. Peakform main runners are manufactured using the patented rotary-stitching process which mechanically binds the double web together giving Peakform™ its unique strength and stability and above all reducing twist. It doesn't stop there, Peakform cartons are lighter making handling and loading easier too.

PeakForm™ - a cut above the rest

The newly designed profile of Peakform makes cutting easier than the traditional square bulb and the cuts themselves are smoother and cleaner.

SECURE

PeakForm™ - locked securely

Superlock is a new feature of Peakform, insertion is easy, more secure and alignment and stability is improved. With a lateral connect and disconnect it is easier to install and remove in low clearance areas or in the centre of a room.



Discover how easy and fast your next installation can be when you choose Peakform.

For more information contact Internal Technical Sales Group.

